

Clase II Class II
FAP 120 DALI-2


FP120-DA2

Fuente de alimentación de tensión constante. Especialmente diseñado para la regulación de tiras de LED mediante señal DALI-2. Regulación del 0% al 100% de la intensidad de salida. Funciona desde 90 ~ 305VAC.


Constant voltage power supply. Specially designed for the regulation of LED strips by DALI-2 signal. Regulation from 0% to 100% of the output intensity. Operates from 90 ~ 305VAC.




Medidas Dimensions



Curva de reducción Derating curve



Características estáticas Static characteristics



Clase II Class II FAP 120 DALI-2

Características técnicas Technical data

		FP120-12-DA2	FP120-24-DA2
Salida Output	Voltaje DC DC Voltage	12V	24V
	Corriente nominal Rated current	10A	5A
	Potencia nominal Rated power	120W	120W
	Rango de regulación Dimming range	0 ~ 100%	
	Frecuencia PWM PWM frequency	1.47kHz for Blank/DA-Type, 2.5kHz for DA2-Type	
	Configuración, Tiempo de subida Setup, Rise time	500ms, 80ms/230VAC or 115VAC	
	Espera tiempo Hold up time	16ms/230VAC or 115VAC	
Entrada Input	Rango de voltaje Voltage range	90 ~ 305VAC 127 ~ 431VDC	
	Rango de frecuencia Frequency range	47 ~ 63Hz	
	Factor de potencia Power factor	PF>0.97/115VAC, PF>0.96/230VAC, PF>0.93/277VAC @ full load	
	Distorsión armónica total Total harmonic distortion	THD<20%(@load>60%/115VAC, 230VAC; @load>75%/277VAC)	
	Eficiencia Efficiency	88.5%	90%
	Corriente AC AC current	1.3A / 115VAC 0.65A / 230VAC 0.55A / 277VAC	
	Corriente de irupción Inrush current	COLD START 60A(twidth=520µs measured at 50% Ipeak) at 230VAC	
Protección Protection	Corriente de fuga Leakage current	<0.25mA / 277VAC	
	Sobrecarga Overload	108 ~ 130% rated output power Hiccup mode or Constant current limiting,recovers automatically after fault condition is removed.	
	Sobre voltaje Over voltage	15 ~ 17V	28 ~ 34V
Ambiente Environment	Temperatura de trabajo Working temperature	-40 ~ +90°C	
	Humedad de trabajo Working humidity	20 ~ 95% RH	
	Temp. almacen., humedad Storage temp.,humidity	-40 ~ +80°C, 10 ~ 95% RH	
	Coefficiente temperatura Temp. coefficient	±0.03%/°C (0 ~ 45°C, except 0 ~ 40°C for 12V)	
	Vibración Vibration	10 ~ 500Hz, 5G 12min./1cycle, period for 72min. each along X, Y, Z axes	
Seguridad Safety & EMC	Estándares de seguridad Safety standards	UL8750(type "HL")(except for 12DA type), CSA C22.2 No. 250.13-12; ENEC BS EN/EN61347-1, BS EN/EN61347-2-13, BS EN/EN62384 independent, IP67,BIS IS15885(for PWM-120-12,24 only), EAC TP TC 004,GB19510.1,-GB19510.14 approved; Design refer to BS EN/EN60335-1; According to BS EN/EN61347-2-13 appendix J suitable for emergency installations	
	Estándares de Dali Dali standards	IEC62386-101, 102, 207,251 for DA/DA2-Type only, Device type 6(DT6)	
	Tensión soportada Withstand voltage	I/P-O/P:3.75KVAC; I/P-DA:1.5KVAC; O/P-DA:1.5KVAC	
	Resistencia al aislamiento Isolation resistance	I/P-O/P: 100M Ohms / 500VDC / 25°C/ 70% RH	
	Emisión EMC EMC emission	Compliance to BS EN/EN55015, BS EN/EN61000-3-2 Class C (@load>60%); BS EN/EN61000-3-3, GB17743 and GB17625.1, EAC TP TC 020	
	Inmunidad EMC immunity	Compliance to BS EN/EN61000-4-2,3,4,5,6,8,11; BS EN/EN61547, light industry level (surge immunity Line-Line 2KV), EAC TP TC 020	

