

# Cougar IP68: special for swimming pools

# Silicone upgrade Now up to 5 years warranty

The Cougar IP68 LED strips by Lluria take a leap in quality and evolve by changing their PVC coating to a silicone one. This new product provides several benefits.

# The volu

# Injected and flus connectors

The connectors are now better integrated, without protruding from the strip volume itself, resulting in a much more aesthetic, easier and simpler installation.



# More efficiency


The lumens of our Cougar range are increased, which allows a higher light intensity for aquatic spaces, thanks to the silicone.



## Temperature resistance

Increased resistance to extreme temperatures. This feature is ideal for applications in environments with thermal contrasts, such as thermal pools or spas, where temperatures can fluctuate dramatically.





# Silicone





## More length

It has increased the length of most LED strips by up to 50%, while maintaining the same connections to the power supplies.



# More reliability

With a thicker PCB (Printed Circuit Board), the reliability of the processor and consequently of the strip is improved.<sup>1</sup>




## Improved performance

Conductivity is improved and performance optimised, thanks to an evolution in electrified rails.  $^{\rm 2}$ 

# Uniformity

The full silicone coating allows the light body to be self-cleaning and anti-UV, as well as maintaining constant illumination.<sup>3</sup>



# Lluria synonymous with quality



# Longevity

Its long life, with more than **50.000 hours of service life**, guarantees less maintenance and replacements.



# Flexibility

Thanks to their flexible design, these strips can be adjusted both **horizontally and vertically** to fit into spaces, allowing for easy adaptation to various pool shapes and sizes.



# Chlorine and salinity resistance

Due to its protection index and its silicone coating, it is perfectly resistant to **chlorine** and **salt water**. This allows for great versatility in aquatic installations of all kinds.



# Variety of colours

They are available in a wide range of colour temperature and colour from **monochromatic, RGB, RGBW, Double White** or **Dim to Warm.** 

# Coming soon... We reduce delivery times

The technological change from PVC to silicone will allow us to make the coating of the Cougar IP68 strips directly at our Montmeló factory. Thanks to this significant improvement we can reduce delivery times to one week.

The local handling of Cougar IP68 strips guarantees not only greater efficiency in production, but also a faster and more effective response to our customers' needs. In this way we strengthen our commitment to customer satisfaction.




# Index





Cougar

D.8





CO12 RGB VS Cougar RGB Vertical bend D.9

CO12 RGB HS Cougar RGB Horizontal bend D.9



Cougar

D.8

Vertical bend

**CO15 RGBW VS** Cougar RGBW Vertical bend p.11



Vertical bend

p.11

Cougar Double White

CO15 RGBW 3LS

Cougar RGBW 3L

Vertical bend

p.13

Horizontal bend





p.12

D.14

Horizontal bend

CO12 3LS Cougar Double White Cougar 3L p.12



CO12 RGB 3LS Cougar RGB 3L Vertical bend D.13



**IP68** Connectors D.16





p.18



Accesories

CO12 18-30 VS Cougar Dim to Warm Vertical bend



CO12 18-30 HS Cougar Dim to Warm Horizontal bend p.14

<b>12</b> W/m	5 Warranty Years	IP 68	IK <b>08</b>	CRI >80	3 MacAdam STEPS	LED SMD 2835	<b>108</b> LED/m	<b>≫</b> 55,6mm
Custom	1130	r min 15cm	<b>24V</b> DC	<b>X</b>	Ú.	5m max.	+55°c -40°c	Silicon 28.085

Cougar Vertical bend



Code	ССТ	Lm/m	Lm/W
C012-22-VS	2200K	450	38
C012-27-VS	2700K	565	47
C012-30-VS	3000K	565	47
C012-40-VS	4000K	580	48
C012-57-VS	5700K	580	48

For other temperatures and colours, please contact us.



SHEET		
		30000mm —
	55.6mm	



16mm

Cougar Horizontal bend

- 16 mm-


17mm


<b>12</b> W/m	5 Warranty Years	IP 68	IK <b>08</b>	CRI >80	<b>3</b> MacAdam STEPS	LED SMD 2835	<b>108</b> LED/m	<b>≫</b> 55,6mm
Custom	116°	r min 15cm	<b>24V</b> DC		Ú.	5m max.	+55°c -40°c	Silicon 28.085

2200K 2700K	380 470	31
2700K	470	20
		39
3000K	470	39
4000K	480	40
5700K	480	40
	4000K 5700K	4000K 480


For other temperatures and colours, please contact us.








CO12 RGB HS	<b>12</b> W/m	5 Warranty Years	IP 68	LED SMD 5050	<b>84</b> LED/m	RGB	<b>%</b> 83,3mm	Custom	∰ 3n1
Cougar RGB		r min 15cm	24V DC	Ŵ	Ć	5m max.	+55°c -40°c	Si 14 SILICON 28.085	
Horizontal bend	118°		DC	<b>PT1</b>		$\approx$		28.085	





### CO15 RGBW VS **15** W/m IP 68 5 Warranty Years 1130 ⊕ 4n1 Cougar RGBW Vertical bend



12-	Code	ССТ	Lm/m Lm/W
A STREET		Red	90
	C015-RGB-27-VS	Green	240
20	C015-RuB-27-VS	Blue	40
		2700K	240
61400 ALTRO		Red	90
	C015-RGB-40-VS	Green	240
	COT2-K0B-40-A2	Blue	40
		4000K	240
DATA SHEET	For other temperatures an	d colours, plea	ase contact us.

83,3mm

- 6550 - 🔲 9

DATA SHEET

**CO12 DW VS** Cougar Double White

Vertical bend

- 16 -17mm

16mm


16mm

<b>12</b> W/m	5 Warranty Years	IP 68	IK <b>08</b>	CRI >80	LED SMD 3015	<b>144</b> LED/m	X 83,3mm	© Custom
116°	r min 15cm	<b>24V</b> DC		Á.	5m max.	+55°c -40°c	Si <sup>14</sup> silicon 28.085	

Code	ССТ	Lm/m	Lm/W
C012-22-57-VS	2200K	220	
012-22-57-95	5700K	270	

For other temperatures and colours, please contact us.





<b>CO12 DW HS</b>	1 W
-------------------	--------

Cougar Double White

Horizontal bend

<b>12</b> W/m	5 Warranty Years	IP 68	IK <b>08</b>	CRI >80	LED SMD 3015	<b>144</b> LED/m	<b>≫</b> 83,3mm	Custom
110°	r min 15cm	<b>24V</b> DC		Á.	5m max.	+55°c -40°c	Si <sup>14</sup> silicon 28.085	

/	Code	ССТ	Lm/m	Lm/W
	(012 22 F7 US	2200K	220	
	C012-22-57-HS	5700K	270	

DATA SHEET



Cougar 3L Vertical bend

.VS	<b>12</b> W/m	5 Warranty Years	IP 68	IK <b>08</b>	CRI >80	<b>3</b> MacAdam STEPS	LED SMD 2835
	Custom	2720	15cm	<b>24V</b> DC	Ŵ	Á.	5m max.
			Code			сст	Lm/r

Code	ССТ	Lm/m	Lm/W	
C012-22-3LS	2200K	850	71	
C012-27-3LS	2700K	1050	88	
C012-30-3LS	3000K	1100	92	
C012-40-3LS	4000K	1100	92	
C012-57-3LS	5700K	1100	92	

**108** LED/m

+55°c -40°c

⊁ 55,6mm


Silicon 28.085


For other temperatures and colours, please contact us.



# **CO12 RGB 3LS**

Cougar RGB 3L Vertical bend





CO15 RGBW 3LS Cougar RGBW 3L Vertical bend

<b>15</b> W/m	5 Warranty Years	IP 68	IK <b>08</b>	LED SMD 5050	<b>84</b> LED/m	RGB	X 83,3mm	Custom
⊕ 4n1	2720	r min 15cm	<b>24V</b> DC		Ú.	5m max.	+55°c -40°c	Si <sup>14</sup> silicon 28.085

	Code	ССТ	Lm/m Lm/W
		Red	110
	C015-RGB-27-3LS	Green	380
	C013-K0B-27-5C3	Blue	70
		2700K	300
		Red	110
	C015-RGB-40-3LS	Green	380
	CO13-N0D-40-5C3	Blue	70
		4000K	300
DATA SHEET	For other temperatures a	nd colours, ple	ease contact us.
	14000mm		

CO12 18-30 VS	<b>12</b> W/m	5 Warranty Years	IP 68	IK <b>08</b>	CRI >80	3 MacAdam STEPS	LED SMD 3015	<b>196</b> LED/m
Cougar Dim to Warm	Custom	1130	r min 15cm	24V DC		Ú.	5m max.	+55°c -40°c

Vertical bend




Code	ССТ	Lm/m	Lm/W
C012-18-30-VS	1800K	3,5	
012-18-30-03	3000K	600	50
1800K			3000


62,5mm

62,5mm

**196** LED/m +55°c -40°c

For other temperatures and colours, please contact us.





16mm

CO12 18-30 HS	<b>12</b> W/m	5 Warranty Years	IP 68	IK <b>08</b>	CRI >80	<b>3</b> MacAdam STEPS	LED SMD 3015
Cougar Dim to Warm Horizontal bend	Custom	113°	r min 15cm	<b>24V</b> DC		Á.	5m max.

Horizontal bend




	,	Lm/W
1800K	3	
3000K	500	42
		3000

For other temperatures and colours, please contact us.





## Connectors IP68 connectors



111210322S     Bottom output IP68 connector with 5m cable       111210323S     Right output IP68 connector with 5m cable       111210324S     Left output IP68 connector with 5m cable       110210320S     IP68 end cap	1112103215	Front output IP68 connector with 5m cable
1112103245 Left output IP68 connector with 5m cable	1112103225	Bottom output IP68 connector with 5m cable
	1112103235	Right output IP68 connector with 5m cable
1102103205 IP68 end cap	1112103245	Left output IP68 connector with 5m cable
	1102103205	IP68 end cap

### CO12-HS

1112113215	Front output IP68 connector with 5m cable
1112113225	Bottom output IP68 connector with 5m cable
1112113235	Right output IP68 connector with 5m cable
1112113245	Left output IP68 connector with 5m cable
1102113205	IP68 end cap

### CO12-RGB-VS

1112103415	Front output IP68 connector with 5m cable
1112103425	Bottom output IP68 connector with 5m cable
1112103435	Right output IP68 connector with 5m cable
1112103445	Left output IP68 connector with 5m cable
1102103405	IP68 end cap

### CO12-RGB-HS

1112113415	Front output IP68 connector with 5m cable
1112113425	Bottom output IP68 connector with 5m cable
1112113435	Right output IP68 connector with 5m cable
1112113445	Left output IP68 connector with 5m cable
1102113405	IP68 end cap

### CO15-RGBW-VS

1112103515	Front output IP68 connector with 5m cable
1112103525	Bottom output IP68 connector with 5m cable
1112103535	Right output IP68 connector with 5m cable
1112103545	Left output IP68 connector with 5m cable
1102103505	IP68 end cap

CO12-DW-VS	
1112113315	Front output IP68 connector with 5m cable
1112113325	Bottom output IP68 connector with 5m cable
1112113335	Right output IP68 connector with 5m cable
111211334S	Left output IP68 connector with 5m cable
1102113305	IP68 end cap
CO12-DW-HS	
1112113315	Front output IP68 connector with 5m cable
1112113325	Bottom output IP68 connector with 5m cable
1112113335	Right output IP68 connector with 5m cable
1112113345	Left output IP68 connector with 5m cable
1102113305	IP68 end cap
CO12-3LS	
1112123215	Front output IP68 connector with 5m cable
1112123225	Bottom output IP68 connector with 5m cable
1112123235	Right output IP68 connector with 5m cable
1112123245	Left output IP68 connector with 5m cable
1102123205	IP68 end cap
CO12-RGB-3LS	
1112123415	Front output IP68 connector with 5m cable
1112123425	Bottom output IP68 connector with 5m cable
1112123435	Right output IP68 connector with 5m cable
1112123445	Left output IP68 connector with 5m cable
1102123405	IP68 end cap
CO15-RGBW-3LS	
1112123515	Front output IP68 connector with 5m cable
1112123525	Bottom output IP68 connector with 5m cable
1112123535	Right output IP68 connector with 5m cable
1112123545	Left output IP68 connector with 5m cable
1102123505	IP68 end cap
CO12-18-30-VS	
1112133215	Front output IP68 connector with 5m cable
1112133225	Bottom output IP68 connector with 5m cable
1112133235	Right output IP68 connector with 5m cable
1112133245	Left output IP68 connector with 5m cable
1102133205	IP68 end cap
CO12-18-30-HS	
1112143215	Front output IP68 connector with 5m cable
1112143225	Bottom output IP68 connector with 5m cable
1112143235	Right output IP68 connector with 5m cable
1112143245	Left output IP68 connector with 5m cable
1102143205	IP68 end cap

# Accessories

## **Cougar vertical bend**





### 1240302007 2m aluminium surface profile

1215202007 20mm profile cut 1240302007






1240303007 2m of aluminium recessed profile

## **Cougar horizontal bend**





1240305007 1m flexible profile aluminium surface

## Cougar 3L









12503070





Metal clamping piece



235001070 Aluminium wall bracket

# **IP68** mounting instructions





# **Cougar Vertical Bend**

Code	
1240302007	2m aluminium surface profile
1215202007	20mm cut-off for 1240302007 profile
1240303007	2m aluminium recessed profile
12503070	Metal clamping piece
234001070	Metal swing clamp
235001070	Aluminium wall bracket

## **Cougar Horizontal Bend**

Code	
1240302007	2m aluminium surface profile
1215202007	20mm cut-off for 1240302007 profile
1240303007	2m aluminium recessed profile
1240305007	1m aluminium recessed flex profile
12503070	Metal clamping piece
234001070	Metal swing clamp
235001070	Aluminium wall bracket

## **Cougar 3L accessories**

Code	
1240302108	2m aluminium-faced profile with transparent sides
1215202108	35mm profile cut-off for 1215202108
234001070	Metal swing clamp
235001070	Aluminium wall bracket





Rec Molinar, 7 (Z.I del Circuit) 08160 Montmeló (**Barcelona**, Spain) +**34 935 938 176** *Iluria.com* 

> Ps. de la Castellana, 91 Planta 4 atrium 28046 **Madrid** (Spain)

